

# Saville DuraLite

## DL-3000 24/7 / DLW-3000 24/7

Designed and built for demanding applications eg control rooms and digital signage. Direct power off plus three year warranty.



- High contrast ratio 2000:1
- Full digital projection with DVI input
- Remote control includes pointer & spotlight
- Networkable with anti-theft monitoring

**DL-3000 24/7**  
**DLW-3000 24/7**

**XGA**  
**WXGA**

**3000 Lumens**  
**3000 Lumens**

**4.1 kg**  
**4.1 kg**

**24/7 Operation**  
**Widescreen 24/7 Operation**

## Specification

Native Resolution / Resizing	XGA (1024 x 768) native resolution up through UXGA (1600 x 1200) with Intelligent ImagaCE resizing	Safety Approval	UL, FCC Class A
TV Lines	600 TV lines (DTV 720P input)	Operating/Storage Temperatures	41° F to 95° F (+5° C to +35° C) / -4° F to 140° F (-20° to +60° C)
Device Type	Single 0.55" DLP® chip	Inputs/Outputs	1 - RGB/component input (15-pin HD); I-DVI-I RGB/HDCP; 1 - composite video input (RCA pin type); 1 - S-Video input (4-pin Din); 1 - PC/Component stereo audio input (3.5mm mini jack); 1 - Video audio input (1-pair RCA pin-type); 1 - RGB loop-through output (15-pin HD); 1 - Stereo VAO line variable audio output (3.5mm mini jack); 1 - RS-232C (9-pin mini DIN);
Cabinet Color	Dark Metallic	USB for mouse control; RJ-45 LAN connector	
H & V Frequency / Dot Clock	fH 15-110 kHz / fv 45-85 Hz / 12-170 MHz	LAN Connectivity	Built-in RJ-45 LAN Connector
Compatibility	PC, Mac®, Workstation	Control Systems	Compatible with Crestron®, AMX®, Extron®, Bitlogix®
Video System	NTSC 3.58, 4.43 / PAL, 60, M, N/SECAM	Included Accessories	Wireless remote control; two AA batteries; 6' AC power cord; 10' RGB signal cable; attached lens cap; integrated air filter; projector operation manual; RS-232C control adapter; storage bag
DTV / HDTV	Compatibility including 480i, 480P, 540P, 576i, 576P, 720P, 1035i, 1080i, 1080P	Optional Accessories	AN-XRCM30 ceiling mount bracket; AN-EP101B extension tube for ceiling mount; AN-JT200 angle mount joint for ceiling mount; AN-CMCS16 16" security cable system; AN-CMCS46 security cable system; AN-C3CP2 3-RCA to 15-pin D-sub cable (10'); AN-A1RS RS-232C adapter; AN-MR2 remote IR receiver (for forward/back presentation control); AN-C3BN 5-BNC to 15-pin D-sub cable (10'); AN-C500SB light-duty storage bag; AN-C600WCC hard-shell wheeled storage bag; AN-C600SC "ATA" storage case
Brightness	3000 ANSI lumens (2400 A.L. in low power eco + quiet mode)	Dimensions	(w x d x h) (in inches) 12-13/32 x 4-19/64 x 11-1/32 (main body only); 12-13/32 x 4-47/64 x 11-37/64 (with adjustment foot & projecting parts)
Contrast Ratio	2000:1	Weight (in pounds)	4.1 kg
Lens Type	1:1.15x manual zoom and focus, F2.4-2.6, throw ratio = 1.75-2.0, f = 18.7-21.5mm	UPC	074000365315
Optical System	Condenser lens optical system (provides higher image uniformity and contrast, without ghosting)		
Aspect Ratio	Native 4:3 (with image shift for 16:9 software)		
Screen Size (Min / Max)	40" (diagonal) up to 300" (diagonal)		
Projection Distance	11.5' x 13.3' (for 100" diagonal screen)		
IR Wireless Remote Control	Yes – with on-screen break timer, GUI pointer, spotlight, forward/back presentation control and mouse control. [38 kHz carrier frequency]		
Built-in Audio System	2.0 Watts monaural		
Lamp Module	AN-F310LP / AN-F310LP/1 (275W DC, user replaceable)		
Estimated Lamp Life	2000 hours / 3000 hours (standard/eco)*1		
Fan Noise (standard/eco)	35dB / 30dB		
Power Source	100 - 240V, 3.7A		
Power Consumption	363W in bright lamp setting and high fan mode; 294W in eco + quiet lamp setting and normal fan mode; 10.5W in standby mode (at 100V AC)		
Heat Dissipation (110V)			
(lamp setting bright/eco/quiet)	1365 BTU/hour / 1110 BTU/hour		

Saville Audio Visual Head Office: Millfield Lane, Nether Poppleton, York YO26 6PQ  
Tel: 0870 606 1100 Fax: 01904 782700 E-mail: head.office@saville-av.com www.saville-av.com

**saville**  
AUDIO VISUAL

FARNBOROUGH GUILDFORD WELWYN CARDIFF COVENTRY MANCHESTER LIVERPOOL LEEDS YORK HULL NORTH EAST EDINBURGH GLASGOW BELFAST