

# Saville PowerLite

## SPI-2600

Compact and affordable new high-bright LCD projector designed for easy installation. UXGA and WXGA compatible with fast power-up and power-down facility.



- 2500 ANSI Lumens
- True XGA resolution (WXGA, UXGA~VGA and MAC compatible)
- Quiet operation: fan noise as low as 28 dB
- Convenient mid-range (1.2:1) manual zoom and focus lens
- Displays 4:3 and 16:9 formats and supports most HDTV resolutions
- Turn OFF and Go!
- 3 Year loan exchange warranty

SPI-2600

XGA

2600 lumens

3.1kg

Installation

## Specification

Screen Brightness	up to 2500 ANSI Lumens	Video Compatibility	NTSC/PAL/SECAM/NTSC 4.43/PAL-M&N
Illumination Uniformity	85%	Video: HD Compatibility	480i/p, 575i/p, 720p, 1035i, 1080i
Size of Color Palette	16.7 Million	Video: Formats Supported	Normal 4:3 and Wide Screen 16:9
Contrast Ratio	450:1 (Full ON/OFF)	Video: Image Sizing	Video Scaling Technology
Projection Lamp	220 Watt UHP	<b>Image Signal Inputs:</b>	
Estimated Lamp Life	up to 3000 Hours of Use	1. Computer In 1/Component In (with optional adapter):	HD15 x 1
Imaging System	0.63" PolySilicon active matrix TFT Panels x 3	2. Computer In 2/Monitor Out: (switchable):	HD15 x 1
Screen Pixels	1024 x 768 in stripe configuration	3. Video In:	RCA x 1 (Composite)/S-Video x 1(Y/C)
Total Pixels	2,359,296 ((1024 x 768) x 3))	<b>Audio Signal Inputs:</b>	
Lens Type	Manual Zoom and Focus	1. Computer 1 & 2/Component:	Stereo: MiniStereo x 1
Lens Specs	Speed: f:1.65 ~ 1.81; FL: 0.886 ~ 1.063 in. (22.5 ~ 27 mm)	2. Composite/S-Video:	RCA x 2 (L&R)
Lens Ratios	Zoom Max:Min: 1.2:1; Throw:Width: 1.72 ~ 2.07:1	Audio: Amplifier	Mono: 1 Watts RMS
Image Diagonal	~ 300 in. (102 ~ 762 cm)	Audio: Output	Stereo: MiniStereo x 1 (Variable)
Image Width	2.6 7 ~ 20 ft. (.84 ~ 6.1 m)	Audio: Built In Speakers	1.1 in. (2.8 cm) x 1
Throw Distance (Wide Tele)	4.6 ~ 41.3 ft. (1.4 ~ 12.6 m)	Fan Noise	as low as 28 dBA
Front Elevation/Maximum Pitch	up to 10° up/up to 10° up or down	Cabinet Size (HxWxD)	**3.1 x 13.2 x 9.4 in. (79.6 x 335 x 238.4 mm)
Anti Keystone	Fixed Image Offset, Ratio (Top:Bottom) 9:1	Weight	(**Excluding legs & lens)
Vertical Keystone Correction	Digital, up to 20° up or down	Packaged Size (HxWxD)	6.8 lbs. (3.1 kg)
Scanning Frequency	Auto: H Sync. 15-100kHz; V Sync. 50-100Hz	Packaged Weight	11.0 lb (5.0 kg)
Dot Clock	140 MHz	Power Requirements	-240V AC, 50/60Hz
Image Orientation	Normal, Reversed, Inverted	Power Consumption	up to 245 Watts
Local Control/Power Management	Full Function/Auto Shut-Down	Heat	up to 836 BTU (211 KC)
Remote Projector Control	Wireless (Infra Red) x 1	Power Cord	10' (3 M) Type 3, Detachable
Service Port (RS-232)	Mini DIN 8 Pin x 1	Electrical Safety Compliance	UL, cUL, IEC
Computer Native Resolution	1024 x 768 (XGA)	Electromagnetic Compliance	FCC Class B, CE Mark
Computer: Compatibility	UXGA, SXGA+, SXGA, WXGA, XGA, SVGA, VGA and MAC	Security Facilities	Kensington® Security Slot
Computer: Formats	1600 x 1200 thru 640 x 480	Operating Temperature	41 ~ 95°F (5 ~ 35°C)
Computer: Higher Resolutions	Displayed panned or Smart Compressed	User Maintenance	Clean Air Filter, Replace Lamp
Computer: Lower Resolutions	Displayed normal or Smart Expanded		

Saville Audio Visual Head Office: Millfield Lane, Nether Poppleton, York YO26 6PQ  
Tel: 0870 606 1100 Fax: 01904 782700 E-mail: head.office@saville-av.com www.saville-av.com

**saville**  
AUDIO VISUAL